




Type HT

ALUMINIUM H-Tap Compression Connectors



Features



- Serrated interior
- Prefilled with oxide inhibitor
- Installed with industry standard "O" and "D" dies
- Rated for 600 Volts, CSA Certified
- Manufactured from high strength aluminum alloy

Benefits

- Assures positive mating with cable strands when compressed
- Provides corrosion resistance
- Provides convenient die selection
- Can be used on any secondary splice or tap application
- Provides maximum conductivity and excellent crimping characteristics

Rated for 600 Volts

"O" and "D" Type Connectors

ILSCO Model Nr.	Main side Wire Range			Tap side Wire Range			Die Index	Dimensions			Cover Model Nr.	Blackburn Model Nr.
	ACSR	Stranded	Solid	ACSR	Stranded	Solid		L (in)	W (in)	H (in)		
HT-6	2 to 6	1 to 6	1 to 6	2 to 6	1 to 6	1 to 6	O	1-1/2	23/32	1-23/32	C-5	WR-159
HT-8	1/0 to 3	2/0 to 2	3/0 to 1	2 to 6	1 to 6	1/0 to 6	O	1-1/2	45/64	1-25/32	C-5	WR-189
HT-2	2/0 to 1/0	3/0 to 2/0	-	2 to 6	1 to 6	1/0 to 6	D ₃	1-7/8	13/16	2-3/16	C-7	WR-289
HT-4	2/0 to 1	3/0 to 1/0	-	2/0 to 1	3/0 to 1/0	-	D ₃	1-7/8	57/64	2-17/64	C-7	WR-279
HT-3	4/0 to 3/0	4/0	-	2 to 6	1 to 6	1/0 to 6	D ₃	1-7/8	53/64	2-1/4	C-7	WR-379
HT-5	4/0 to 3/0	4/0 to 3/0	-	2/0 to 1	2/0 to 1/0	-	D ₃	2-1/4	53/64	2-3/8	C-7	WR-399
HT-7	4/0 to 3/0	4/0 to 3/0	-	4/0 to 3/0	4/0 to 3/0	-	D ₃	2-1/2	7/8	2-1/2	C-7	WR-419
KO-R24	4 to 2/0	4 to 2/0	-	-	10	10 to 6	O	1-1/16	23/32	1-7/64	C-7	WR-139
			-	-	-	14 to 10						
KD-R28	2/0, 3/0, 4/0	3/0,4/0	-	2/0, 3/0, 4/0	3/0,4/0	-	D ₃				C-7	WR-419
KN-8	300, 336.4, 397.5, 477-18/1	336.4, 350, 397.5, 400, 450, 477, 500	-	266.8, 300, 336.4-18/1	250, 266.8, 300, 336.4, 350	-	N	3-1/2	1-1/4	2		WR-885
			#ND-58 Crimping toll for above. Has dies "O" and "D3" included							#W-BG Dies sold separately. Fits on jaws of #ND-58 Tool		